

KI-N4058

4U Compact Stylish Rackmount Chassis



Introduction

4U industrial rackmount chassis KI-N4058. It supports up to seven full-length full-height add-on cards. Total capacity up to 3 x 5.25" + 8 x 3.5" (internal) drives for high density data storage. 1*12cm+2*80mm fan provides excellent thermal cooling solution. Achieve ultimate uninterrupted operation with support redundant power supply or PS-2 Powersupply. KI-N4048 provides your server or cluster maximum flexibility and performance.

Features and Benefits

- ▶ Industrial chassis for 12"*10.5" M/B or 14/15slot passive backplane
- ▶ 3 x 5.25" + 8 x 3.5" (internal)
- ▶ Aluminum Alloy front door, both are lockable, Air filter are Removable & Washable
- ▶ Front access USB2.0*2
- ▶ Standard I/O shield
- ▶ Optional DVR rear panel
- ▶ Power and HDD LED



Option: Ball bearing rail kit



Dimension (W*H*D)	19"*7"*18.9"/ 485*177*480mm
Material Construction	Heavy-duty and anti-rusty SECC steel T=1.2mm,Aluminum front door T=3.0mm
M/B Size	(ATX) 12"*10.5" or 14/15slot passive backplane
Expansion	7 slots rear side full height or DVR rear panel
Control & Indicator	1*Power switch +1* Reset switch
	1 x LED (power) +1 x LED (HDD)
	1*2.0 USB
Cooling Fans	1*12cm Fan in front+2*6cm Fan(optional)
DriveBay	3 x 5.25" + 8 x 3.5" (internal)
Power Supply	Standard PS-2 ATX or PS-2 size Mini-Redundant
	Power supply 300w~550w
Sliding rail	20" ball bearing sliding rail (option)
Color	Black / Red / Bule / Green / Silver
Operation Temperature	Up to 50C (122°F)
Operation Humidity (Non-condensing)	Up to 90%
Packing Measurement CBF / CBM	2.7 / 0.076
Packing N.W / G.W	13.0KGS /15.0KGS

